



Technische Eigenschaften

Technical characteristics / caractéristiques techniques
Características técnicas / Caratteristiche tecniche
Características técnicas



10A, 2300W



Kompatibilität

Compatibility / Compatibilité
Compatibilidad / Compatibilità
Compatibilidade



Eglo Connect AwoX SmartPLUG Mesh

Weitere Informationen finden
Sie in der Bedienungsanleitung

For more information, read the user guide
Pour plus d'information, lire le mode d'emploi
Para obtener más información, consulte el manual de instrucciones
Per ulteriori informazioni consultare le istruzioni per l'uso
Para obter mais informações, consulte o manual de instruções




Support : <http://www.eglo.com/connect>
<http://www.awox.com/user-guides>



v3



PLUG



1



Laden Sie die App herunter SmartCONTROL

Download SmartCONTROL app
Télécharger l'application SmartCONTROL
Descargue la aplicación SmartCONTROL
Scarica l'app SmartCONTROL
Faça o download da aplicação SmartCONTROL

AwoX SmartControl




2



Fügen Sie ein Gerät in der App hinzu

Add a device in app
Ajouter une ampoule dans l'app
Agregue un dispositivo a la aplicación
Aggiungi un dispositivo nella app
Adicione um dispositivo à aplicação




3

Folgen Sie dem Assistenten
Follow the wizard / Suivre l'assistant
Siga las instrucciones del asistente
Segui le indicazioni della guida
Siga as instruções do assistente




1



2

Stecken Sie den SmartPLUG in die Steckdose
Plug the SmartPLUG into the main socket
Branchez le SmartPLUG dans la prise principale
Enchufe el SmartPLUG
Inserisci lo SmartPLUG nella presa della corrente
Ligue o SmartPLUG à tomada




3



3 Sekunden lang drücken um deinen Stecker von deiner Fernbedienung aus zu steuern

3 seconds long press
to control your plug from your remote
Appui long de 3 secondes
pour contrôler votre prise avec votre télécommande



Pulse durante 3 segundos
para poder controlar el conector desde el mando a distancia
Tieni premuto 3 secondi
il tasto per controllare la presa con il telecomando
Pressione durante 3 segundos
para poder controlar o conector com comando